



수신모듈(controller)



수신반

제품사양 SPECIFICATIONS

항목(ITEMS)	사양(SPECIFICATION)	항목(ITEMS)	사양(SPECIFICATION)
제품구조 (Installation Method)	판넬화장형	감지기 연결채널수 (Connection Channel)	2~N회로(Multi Channel)
표시화면 (Measuring Display)	4-Digit FND(LEL, %, VOL, ppm) & Bar Graph	표시화면 (Operating Display)	Alarm 1,2,3(Yellow), Fault(Red), Power(Green)
경보출력(Alarm Signal)	3-Alarm Lamp & Buzzer(75dB/1m)	경보응답속도 (Reponse Time)	< 30 sec, 90%/Full scale
입력신호(Input Signal)	4-20mA, RS-485 MODBUS	출력신호(Output Signal)	RS-485 MODBUS DIGITAL OUTPUT(Optional) RELAY CONTACT OUTPUT 4-20mA, DC voltage(12V)
주전원(Main Power)	AC 220V 50/60 Hz	작동전원(Operating Power)	DC 24V
소비전력(Power Consumption)	4.5 W Max.	정전보상 (Back up Battery)	Ni-Cd 축전지 또는 UPS장치 (OPTION)
작동온도 (Operation Temperature)	-20~60 °C	작동습도 (Operation Humidity)	5~99% RH (Non-condensing)
재질(Body material)	SPCC 1.6t	중량(Module Weight)	1.2 kg
크기(Module Dimension)	90(W) x 144(H) x 54(D) mm	외함크기(Panel Dimension)	외함크기 참조

▶ GRD-4812 (수신부) 외형도

